

Bayesian Data-Analysis Toolbox
Release 4.23, Manual Version 3

G. Larry Bretthorst
Biomedical MR Laboratory
Washington University School Of Medicine,
Campus Box 8227
Room 2313, East Bldg.,
4525 Scott Ave.
St. Louis MO 63110
<http://bayes.wustl.edu>
Email: gbretthorst@wustl.edu

September 18, 2018

Chapter 2

Unknown Number of Exponentials

The unknown number of exponentials package estimates amplitudes and decay rate constants of an unknown number of exponential signal components in data that are known to contain sums of exponential signals. The data analyzed by this package are Ascii data files and may be input as Ascii files, peak picks, the amplitudes from a Bayes Analyze analysis run or extracted from an image stack. The unknown number of exponentials package is accessed by selecting the “Exponential” package on the package menu. When the Exponential package is selected, the interface shown in Fig. 2.1 is displayed. This interface is used in both the given and unknown number of exponentials packages. The unknown number of exponential package is selected by setting the model order to “Unknown”. Note when the model order is set to unknown, the “Constant” widget is grayed out, i.e., becomes inactive because the unknown number of exponentials package computes, among other things, the posterior probability a constant is present. To use the unknown number of exponentials package, you must do the following:

Select the exponential package from the Package menu.

Load one or more Ascii data sets using the Files menu.

Set the “Unknown” model order in the model order selection menu.

Check the Find Outliers check box if you suspect outliers are present in the data.

Review the prior probabilities assignment for the decay rate constants using the Prior Viewer.

Select the server that is to process the analysis.

Check the status of the selected server to determine if the server is busy, change to another server if the selected server is busy.

Run the the analysis on the selected server by activating the Run button.

Get the the results of the analysis by activating the Get Job button. If the analysis is running, this button will return the Accepted report containing the status of the current run. Otherwise, it will fetch and display the results from the current analysis.

Figure 2.1: The Unknown Exponential Interface




Figure 2.1: When the Exponential package is selected, the Exponentials interface is displayed. The unknown number of exponentials package is selected by setting the model order to “Unknown”. The prior viewer can be used to set the prior probability for the decay rate constants. Note in this package the posterior probabilities are marginal posterior probabilities, so there are no adjustable prior probabilities for the amplitudes.

2.1 The Bayesian Calculations

The Bayesian calculation is for the joint posterior probability for the number of exponentials and whether or not a constant offset is present in the data. As with all Bayesian calculations, one begins by relating the data to the parameters of interest. In this case the model which relates the unknown number of exponentials to the data is of the form

$$d_{ij} = C_j + \sum_{l=1}^m A_{lj} \exp\{-\alpha_l t_i\} + n_{ij} \quad (2.1)$$

where d_{ij} is the i th data value in the j th data set containing N_j data values. Note that the number of data values is data set dependent and may differ from one data set to the next, C_j is a constant offset in the j th data set and part of the calculation is to determine if this constant is present, m is the unknown number of exponentials, A_{lj} is the amplitude or intensity of the l th exponential in the j th data set, α_l is the l th exponential decay rate constant, and n_{ij} is noise in the i th data value in the j th data set. Except for the lack of prior information about the number of exponentials m , and whether or not the constant C is present, this is the given number of exponentials model, Eq. (1.1). However, now the Bayesian calculations are more substantial because both m and whether or not C_j are present must be part of the Bayesian calculation.

The calculation begins by first ranked the models from the simplest to the most complicated and then numbering them from 1 to the total number of models. In the program that implements this calculation the maximum number of exponentials is set to 4, consequently there are a total of 10 models. The model number is designated as u and when $u = 1$, the model is no exponential and no constant, $u = 2$ is no exponential and a constant, $u = 3$ is one exponential and no constant, etc., up to model 10, 4 exponentials and a constant. The model indicator, u , is a discrete hypotheses that must be incorporated into the Bayesian calculation and its numerical value indicates both the number of exponentials and whether or not a constant offset is present.

To determine the model, i.e., estimates u , one computes the posterior probability for the model indicator given the data and the prior information, $P(u|DI)$. This posterior probability is computed by an application of Bayes' theorem [1],

$$P(u|DI) = \frac{P(u|I)P(D|uI)}{P(D|I)} \quad (2.2)$$

where $P(u|I)$ is the prior probability for the model indicator, $P(D|uI)$ is the marginal direct probability for the data given the model indicator, and the denominator is

$$P(D|I) = \sum_u P(Du|I) = \sum_u P(u|I)P(D|uI) \quad (2.3)$$

is the normalization constant needed to ensure the total probability for the model indicator sums to one. If this posterior probability is normalized at the end of the calculation, then

$$P(u|DI) \propto P(u|I)P(D|uI). \quad (2.4)$$

The two terms on the right-hand side of this equation are the prior probability for the model indicator, $P(u|I)$, which can be assigned using a uniform prior probability, and the direct probability for all of the data given the model indicator, $P(D|uI)$, which is much too complicated to see how it

should be assigned. However, this direct probability can be computed from the joint probability for all of the data and the parameters given the model indicator, $P(D\{A\}\{\alpha\}\{C\}\{\sigma\}|uI)$, by application of the sum rule:

$$P(u|DI) \propto P(u|I) \int d\{A\}d\{C\}d\{\alpha\}d\{\sigma\}P(D\{A\}\{C\}\{\alpha\}\{\sigma\}|uI) \quad (2.5)$$

where all of the parameters except the model indicator have been removed by marginalization. The notation $\{\cdot\}$, means all of the parameters of the indicated type. So for example $\{A\}$ means all of the amplitudes appearing in the model. If there are 3 exponentials and 5 data sets there would be 15 total amplitudes. Also note that the parameters represented by $\{C\}$ may or may not occur in any given model depending on the model indicator. So if the model indicator is even then $\{C\}$ is present, otherwise its not. The right-hand side of this equation may be factored, one obtains

$$P(u|DI) \propto P(u|I) \int d\{A\}d\{\alpha\}d\{C\}d\{\sigma\}P(\{A\}\{\alpha\}\{C\}\{\sigma\}|uI)P(D|u\{A\}\{\alpha\}\{C\}\{\sigma\}I) \quad (2.6)$$

where $P(\{A\}\{\alpha\}\{C\}\{\sigma\}|uI)$ is the joint prior probability for all of the parameters appearing in model u and $P(D|u\{A\}\{\alpha\}\{C\}\{\sigma\}I)$ is the direct probability for all of the data given all of the parameters and the model indicator. Both of these probabilities are too complicated to see how they might be assigned, but the rules of probability theory can be used to factor these probabilities into increasingly simple terms: Assuming logical independence, i.e., changing the prior information about the amplitudes would not change the prior information about the decay rate constants, standard deviations, etc., then the joint prior probability for all of the parameters, $P(\{A\}\{\alpha\}\{C\}\{\sigma\}|I)$ can be factored into a series of independent prior probabilities for each parameter:

$$P(\{A\}\{\alpha\}\{C\}\{\sigma\}|I) = \left[\prod_{j=1}^m \prod_{k=1}^n P(A_{kj}|I) \right] \left[\prod_{j=1}^m P(\alpha_j|I) \right] \left[\prod_{k=1}^n P(C_k|I) \right] \left[\prod_{k=1}^n P(\sigma_k|I) \right] \quad (2.7)$$

where m is the number of exponentials in the model indicated by u , n is the number of data sets, $P(A_{kj}|I)$ is the prior probability for amplitude k in data set j , $P(\alpha_j|I)$ is the prior probability for the j th decay rate constant, $P(C_k|I)$ is the prior probability for the constant offset in the k th data set, and $P(\sigma_k|I)$ is the prior probability for the standard deviation of the noise in the k th data set. Note, that the prior probability for the constant offset, $P(C_k|I)$, is only present when the model indicator is even. Also note that the dependence on the model indicator has been dropped in these priors, because knowing the number of exponentials and whether or not a constant is present would not change the prior information about the amplitudes and decay rate constants. Substituting the

prior, Eq. (2.7) back into the posterior, Eq. (2.6) to obtain

$$\begin{aligned}
P(u|DI) &\propto P(u|I) \int d\{A\}d\{\alpha\}d\{C\}d\{\sigma\} \\
&\times \left[\prod_{j=1}^m \prod_{k=1}^n P(A_{kj}|I) \right] \\
&\times \left[\prod_{j=1}^m P(\alpha_j|I) \right] \\
&\times \left[\prod_{k=1}^n P(C_k|I) \right] \\
&\times \left[\prod_{k=1}^n P(\sigma_k|I) \right] \\
&\times \left[\prod_{k=1}^n P(D_k|uA_{1k} \dots A_{mk}\{\alpha\}C_k\sigma_k I) \right]
\end{aligned} \tag{2.8}$$

as the posterior probability for the model indicator, where $P(D_k|uA_{1k} \dots A_{mk}\{\alpha\}C_k\sigma_k I)$ is the direct probability for data set D_k given both the parameters that occur in all data sets, the $\{\alpha\}$, and the parameters specific to data set D_k . These data set specific parameters are the constant offset C_k and the amplitudes of the m exponentials in the k th data set. Here these amplitudes have been designated as $A_{1k} \dots A_{mk}$.

If you examine the integrand of this posterior, you will discover that it is the joint posterior probability for the parameters given the model indicator. Consequently, this integrand is exactly the same as the integrand in the joint posterior probability given the model order, Eq. (1.3), and in what follows the same prior probabilities will be assigned in both problems. This will have the effect of making the parameter estimates from the unknown number of exponentials and the given number of exponentials essentially identical when the model indicators are the same.

Equation. (2.8) cannot be further simplified and the only recourse is to assign the various prior probabilities and evaluate the integrals. The prior probability for the model indicator, $P(u|I)$, was assigned using a uniform prior probability:

$$P(u|I) \propto \begin{cases} \frac{1}{10} & \text{if } 1 \leq u \leq 10 \\ 0 & \text{otherwise} \end{cases} . \tag{2.9}$$

The prior probability for the noise standard deviation, $P(\sigma_k|I)$, was assigned a Jeffreys' prior

$$P(\sigma_k|I) \propto \frac{1}{\sigma_k}. \tag{2.10}$$

Note that the Jeffreys' prior has not been bounded and normalized because the exact same normalization constant appears in all models tested by this calculation. The prior probabilities for the

amplitudes, $P(A_{jk}|I)$, are assigned broad Gaussian prior probability:

$$P(A_{jk}|I) = \left(\frac{2\pi\sigma_k^2}{\delta^2}\right)^{-\frac{1}{2}} \exp\left\{-\frac{\delta^2}{2\sigma^2}A_{jk}^2\right\} \quad (2.11)$$

where δ/σ_k plays the part of the standard deviation of this prior probability and cannot be changed by the user. In the program that implements this calculation $\delta = 0.01$.

The prior probabilities for the decay rate constants are under user control and the user may select the type of prior used. However, if the user does not set the prior probability for the decay rate constants, then the same default prior probability described in Chapter 1 Eq. (1.4) is used.

The model equation is symmetric under relabeling of the amplitudes and decay rate constants. This symmetry causes the joint posterior probability for the decay rate constants to be symmetric in the sense that if there is a peak at $\alpha_1 = \beta$ and $\alpha_2 = \gamma$, then there is also a peak at $\alpha_1 = \gamma$ and $\alpha_2 = \beta$; this symmetry is caused because the model does not tell us which exponential signal corresponds to to which model component. Consequently, a convention must be introduced which brakes this symmetry by identifying a model component with a signal component. This is done by forcing the decay rate constants to be ordered.

The full Bayesian calculation and the assignment of the prior probabilities is discussed in reference [16] and this paper is available in pdf by activating [this link](#). Additionally, much more about exponential parameter estimation is contained in [15, 17]. The [first](#) paper describes the problem when the exponential model is given and is a simpler version of this problem, while the [second](#) paper discusses how the accuracy of the parameter estimates depends on the number of data values, signal-to-noise level and the rate of decay of the sample.

2.2 Outputs From The Unknown Number of Exponentials Package

The Text outputs from the unknown number of exponentials package consist of: “Bayes.prob.model,” “BayesExpGiven.mcmc.values,” “Bayes.params,” “Console.log,” “Bayes.accepted” and a condensed output file “Bayes.Condensed.File.” These output files can be viewed using the Text Viewer or they can be viewed using File Viewer by navigating to the current working directory and then selecting the files. The format of the mcmc.values report is discussed in Appendix D and the other reports are discussed in Chapter ??.

When the unknown number of exponentials package is running, the distribution of simulations having a given model indicator u is in constant flux. The unknown number of exponentials program writes the number of simulations having $u = 1$, $u = 2$, etc. to the console log after it completes each annealing step. This display serves as a kind of visual picture of the calculation of the posterior probability for the model indicator. A sample of this output is shown in Fig. 2.2. This listing was generated from a data set that contains three exponential plus a constant. When the annealing parameter is zero, the distribution of simulations reflects only the prior probability for the model. Because that prior probability is uniform, the simulations are essentially evenly distributed across all models. As the program runs, the annealing parameter is increased and the distribution of simulations begins to change to reflect the increasing importance of the likelihood. Typically the simulations begin to cluster around one or two models. This clustering continues until of the simulations have settled into the posterior probability for the model indicator.

Figure 2.2: The Distribution Of Models

Phase	Annl Param	<Likelihood>	<StdDevLike>	0	0+C	1	1+C	2	2+C	3	3+C	4	4+C
Annealing	0.000	-7.2157E+02	1.5195E+02	12	6	7	8	12	13	9	11	10	12
	2	0.005	-5.6842E+02	1.6292E+02	7	5	4	4	2	21	4	24	3
	3	0.011	-4.8783E+02	1.1564E+02	1	0	0	2	0	14	13	28	16
	4	0.018	-4.3429E+02	8.3983E+01	0	0	1	0	0	18	2	29	17
	5	0.026	-3.9971E+02	5.2703E+01	0	0	0	0	0	9	4	26	21
	6	0.038	-3.8265E+02	3.4063E+01	0	0	0	0	0	8	2	37	21
	7	0.054	-3.7660E+02	3.6781E+01	0	0	0	0	0	7	2	34	24
	8	0.069	-3.6507E+02	1.7327E+01	0	0	0	0	0	4	0	39	24
	9	0.090	-3.6031E+02	1.3435E+01	0	0	0	0	0	1	0	44	24
	10	0.113	-3.5629E+02	8.9340E+00	0	0	0	0	0	1	0	54	21

Phase	Annl Param	<Likelihood>	<StdDevLike>	0	0+C	1	1+C	2	2+C	3	3+C	4	4+C
Annealing	0.745	-3.4957E+02	1.5147E+00	0	0	0	0	0	0	0	97	2	1
	32	0.777	-3.4935E+02	1.2221E+00	0	0	0	0	0	0	94	1	5
	33	0.809	-3.4936E+02	1.1754E+00	0	0	0	0	0	0	99	0	1
	34	0.841	-3.4917E+02	9.8822E-01	0	0	0	0	0	0	94	1	5
	35	0.873	-3.4893E+02	8.6573E-01	0	0	0	0	0	0	99	1	0
	36	0.906	-3.4926E+02	1.3015E+00	0	0	0	0	0	0	97	1	2
	37	0.938	-3.4910E+02	9.9978E-01	0	0	0	0	0	0	97	0	3
	38	0.970	-3.4902E+02	9.6721E-01	0	0	0	0	0	0	97	2	1
	39	1.000	-3.4903E+02	9.9140E-01	0	0	0	0	0	0	100	0	0

Figure 2.2: While the unknown number of exponentials package is running, it prints a listing that shows the distribution of the model indicator as a function of the annealing parameter. The 10 columns to the right are the number of simulations in model 0, 1, etc. As the annealing parameter increases these should cluster into one or two columns and the distribution of these simulations is the posterior probability for the model order. In this example the data were three exponentials plus a constant. Notice that as soon as the annealing parameter begins to increase the simulations quickly move to high order models and eventually they all end up in the three exponential plus a constant model.

In addition to these text reports there is one new plot result, the posterior probability for the model order, Fig. 2.3. The abscissa is labeled with the model order. These model orders, 1, 2, 3, etc. are the number of exponentials in the model. When a constant is present this, the model order is changed to 1+C, 2+C, 3+C etc. to indicate the presence of one, two or three exponentials plus a constant. The vertical axis, is the posterior probability for the model indicator. Each probability is computed by counting the number of simulations having the indicated model divided by the total number of simulations. The “Plot Results Viewer” can be used to view the probability for the model indicator and the output probability density functions for the parameters in a given model order. In addition to the standard data, model and residual plots there are probability density functions for the decay rate constants, decay times, the amplitudes for each data set for each exponential and finally there are probability density functions for the standard deviation of the noise in each data set.

Figure 2.3: The Posterior Probability For Exponential Model




Figure 2.3: When the Unknown number of Exponentials package runs a new output plot is produced. The plot is of the posterior probability for the model order. The abscissa is labeled with the model order. These model orders are arbitrated as 1, 2, 3, etc. when the model is one, two or three exponentials without a constant. When a constant is present this label is changed to 1+C, 2+C, 3+C etc. to indicate the presence of one, two or three exponentials plus a constant.

Bibliography

- [1] Rev. Thomas Bayes (1763), “An Essay Toward Solving a Problem in the Doctrine of Chances,” *Philos. Trans. R. Soc. London*, **53**, pp. 370-418; reprinted in *Biometrika*, **45**, pp. 293-315 (1958), and *Facsimiles of Two Papers by Bayes*, with commentary by W. Edwards Deming, New York, Hafner, 1963.
- [2] G. Larry Bretthorst (1988), “Bayesian Spectrum Analysis and Parameter Estimation,” in *Lecture Notes in Statistics*, **48**, J. Berger, S. Fienberg, J. Gani, K. Krickenberg, and B. Singer (eds), Springer-Verlag, New York, New York.
- [3] G. Larry Bretthorst (1990), “An Introduction to Parameter Estimation Using Bayesian Probability Theory,” in *Maximum Entropy and Bayesian Methods*, Dartmouth College 1989, P. Fougère ed., pp. 53-79, Kluwer Academic Publishers, Dordrecht the Netherlands.
- [4] G. Larry Bretthorst (1990), “Bayesian Analysis I. Parameter Estimation Using Quadrature NMR Models” *J. Magn. Reson.*, **88**, pp. 533-551.
- [5] G. Larry Bretthorst (1990), “Bayesian Analysis II. Signal Detection And Model Selection” *J. Magn. Reson.*, **88**, pp. 552-570.
- [6] G. Larry Bretthorst (1990), “Bayesian Analysis III. Examples Relevant to NMR” *J. Magn. Reson.*, **88**, pp. 571-595.
- [7] G. Larry Bretthorst (1991), “Bayesian Analysis. IV. Noise and Computing Time Considerations,” *J. Magn. Reson.*, **93**, pp. 369-394.
- [8] G. Larry Bretthorst (1992), “Bayesian Analysis. V. Amplitude Estimation for Multiple Well-Separated Sinusoids,” *J. Magn. Reson.*, **98**, pp. 501-523.
- [9] G. Larry Bretthorst (1992), “Estimating The Ratio Of Two Amplitudes In Nuclear Magnetic Resonance Data,” in *Maximum Entropy and Bayesian Methods*, C. R. Smith et al. (eds.), pp. 67-77, Kluwer Academic Publishers, the Netherlands.
- [10] G. Larry Bretthorst (1993), “On The Difference In Means,” in *Physics & Probability Essays in honor of Edwin T. Jaynes*, W. T. Grandy and P. W. Milonni (eds.), pp. 177-194, Cambridge University Press, England.
- [11] G. Larry Bretthorst (1996), “An Introduction To Model Selection Using Bayesian Probability Theory,” in *Maximum Entropy and Bayesian Methods*, G. R. Heidbreder, ed., pp. 1-42, Kluwer Academic Publishers, Printed in the Netherlands.

- [12] G. Larry Bretthorst (1999), “The Near-Irrelevance of Sampling Frequency Distributions,” in *Maximum Entropy and Bayesian Methods*, W. von der Linden *et al.* (eds.), pp. 21-46, Kluwer Academic Publishers, the Netherlands.
- [13] G. Larry Bretthorst (2001), “Nonuniform Sampling: Bandwidth and Aliasing,” in *Maximum Entropy and Bayesian Methods in Science and Engineering*, Joshua Rychert, Gary Erickson and C. Ray Smith *eds.*, pp. 1-28, American Institute of Physics, USA.
- [14] G. Larry Bretthorst, Christopher D. Kroenke, and Jeffrey J. Neil (2004), “Characterizing Water Diffusion In Fixed Baboon Brain,” in *Bayesian Inference And Maximum Entropy Methods In Science And Engineering*, Rainer Fischer, Roland Preuss and Udo von Toussaint *eds.*, AIP conference Proceedings, **735**, pp. 3-15.
- [15] G. Larry Bretthorst, William C. Hutton, Joel R. Garbow, and Joseph J.H. Ackerman (2005), “Exponential parameter estimation (in NMR) using Bayesian probability theory,” *Concepts in Magnetic Resonance*, 27A, Issue 2, pp. 55-63.
- [16] G. Larry Bretthorst, William C. Hutton, Joel R. Garbow, and Joseph J. H. Ackerman (2005), “Exponential model selection (in NMR) using Bayesian probability theory,” *Concepts in Magnetic Resonance*, 27A, Issue 2, pp. 64-72.
- [17] G. Larry Bretthorst, William C. Hutton, Joel R. Garbow, and Joseph J.H. Ackerman (2005), “How accurately can parameters from exponential models be estimated? A Bayesian view,” *Concepts in Magnetic Resonance*, 27A, Issue 2, pp. 73-83.
- [18] G. Larry Bretthorst, W. C. Hutton, J. R. Garbow, and Joseph J. H. Ackerman (2008), “High Dynamic Range MRS Time-Domain Signal Analysis,” *Magn. Reson. in Med.*, **62**, pp. 1026-1035.
- [19] V. Chandramouli, K. Ekberg, W. C. Schumann, S. C. Kalhan, J. Wahren, and B. R. Landau (1997), “Quantifying gluconeogenesis during fasting,” *American Journal of Physiology*, **273**, pp. H1209-H1215.
- [20] R. T. Cox (1961), “The Algebra of Probable Inference,” Johns Hopkins Univ. Press, Baltimore.
- [21] André d’Avignon, G. Larry Bretthorst, Marilyn Emerson Holtzer, and Alfred Holtzer (1998), “Site-Specific Thermodynamics and Kinetics of a Coiled-Coil Transition by Spin Inversion Transfer NMR,” *Biophysical Journal*, **74**, pp. 3190-3197.
- [22] André d’Avignon, G. Larry Bretthorst, Marilyn Emerson Holtzer, and Alfred Holtzer (1999), “Thermodynamics and Kinetics of a Folded-Folded Transition at Valine-9 of a GCN4-Like Leucine Zipper,” *Biophysical Journal*, **76**, pp. 2752-2759.
- [23] David Freedman, and Persi Diaconis (1981), “On the histogram as a density estimator: L_2 theory,” *Zeitschrift für Wahrscheinlichkeitstheorie und verwandte Gebiete*, **57**, 4, pp. 453-476.
- [24] W. R. Gilks, S. Richardson, and D. J. Spiegelhalter (1996), “Markov Chain Monte Carlo in Practice,” Chapman & Hall, London.

- [25] Paul M. Goggans, and Ying Chi (2004), "Using Thermodynamic Integration to Calculate the Posterior Probability in Bayesian Model Selection Problems," in *Bayesian Inference and Maximum Entropy Methods in Science and Engineering: 23rd International Workshop*, **707**, pp. 59-66.
- [26] Marilyn Emerson Holtzer, G. Larry Bretthorst, D. André d'Avignon, Ruth Hogue Angelette, Lisa Mints, and Alfred Holtzer (2001), "Temperature Dependence of the Folding and Unfolding Kinetics of the GCN4 Leucine Lipper via ^{13}C alpha-NMR," *Biophysical Journal*, **80**, pp. 939-951.
- [27] E. T. Jaynes (1968), "Prior Probabilities," *IEEE Transactions on Systems Science and Cybernetics*, SSC-4, pp. 227-241; reprinted in [30].
- [28] E. T. Jaynes (1978), "Where Do We Stand On Maximum Entropy?" in *The Maximum Entropy Formalism*, R. D. Levine and M. Tribus *Eds.*, pp. 15-118, Cambridge: MIT Press, Reprinted in [30].
- [29] E. T. Jaynes (1980), "Marginalization and Prior Probabilities," in *Bayesian Analysis in Econometrics and Statistics*, A. Zellner *ed.*, North-Holland Publishing Company, Amsterdam; reprinted in [30].
- [30] E. T. Jaynes (1983), "Papers on Probability, Statistics and Statistical Physics," a reprint collection, D. Reidel, Dordrecht the Netherlands; second edition Kluwer Academic Publishers, Dordrecht the Netherlands, 1989.
- [31] E. T. Jaynes (1957), "How Does the Brain do Plausible Reasoning?" unpublished Stanford University Microwave Laboratory Report No. 421; reprinted in *Maximum-Entropy and Bayesian Methods in Science and Engineering* **1**, pp. 1-24, G. J. Erickson and C. R. Smith *Eds.*, 1988.
- [32] E. T. Jaynes (2003), "Probability Theory—The Logic of Science," edited by G. Larry Bretthorst, Cambridge University Press, Cambridge UK.
- [33] Sir Harold Jeffreys (1939), "Theory of Probability," Oxford Univ. Press, London; Later editions, 1948, 1961.
- [34] John G. Jones, Michael A. Solomon, Suzanne M. Cole, A. Dean Sherry, and Craig R. Malloy (2001) "An integrated ^2H and ^{13}C NMR study of gluconeogenesis and TCA cycle flux in humans," *American Journal of Physiology, Endocrinology, and Metabolism*, **281**, pp. H848-H856.
- [35] John Kotyk, N. G. Hoffman, W. C. Hutton, G. Larry Bretthorst, and J. J. H. Ackerman (1992), "Comparison of Fourier and Bayesian Analysis of NMR Signals. I. Well-Separated Resonances (The Single-Frequency Case)," *J. Magn. Reson.*, **98**, pp. 483-500.
- [36] Pierre Simon Laplace (1814), "A Philosophical Essay on Probabilities," John Wiley & Sons, London, Chapman & Hall, Limited 1902. Translated from the 6th edition by F. W. Truscott and F. L. Emory.
- [37] N. Lartillot, and H. Philippe (2006), "Computing Bayes Factors Using Thermodynamic Integration," *Systematic Biology*, **55** (2), pp. 195-207.

- [38] D. Le Bihan, and E. Breton (1985), “Imagerie de diffusion in-vivo par rsonance,” Comptes rendus de l’Acadmie des Sciences (Paris), **301** (15), pp. 1109-1112.
- [39] N. R. Lomb (1976), “Least-Squares Frequency Analysis of Unevenly Spaced Data,” *Astrophysical and Space Science*, **39**, pp. 447-462.
- [40] T. J. Loredo (1990), “From Laplace To SN 1987A: Bayesian Inference In Astrophysics,” in *Maximum Entropy and Bayesian Methods*, P. F. Fougere (ed), Kluwer Academic Publishers, Dordrecht, The Netherlands.
- [41] Craig R. Malloy, A. Dean Sherry, and Mark Jeffrey (1988), “Evaluation of Carbon Flux and Substrate Selection through Alternate Pathways Involving the Citric Acid Cycle of the Heart by ^{13}C NMR Spectroscopy,” *Journal of Biological Chemistry*, **263** (15), pp. 6964-6971.
- [42] Craig R. Malloy, Dean Sherry, and Mark Jeffrey (1990), “Analysis of tricarboxylic acid cycle of the heart using ^{13}C isotope isomers,” *American Journal of Physiology*, **259**, pp. H987-H995.
- [43] Lawrence R. Mead and Nikos Papanicolaou, “Maximum entropy in the problem of moments,” *J. Math. Phys.* **25**, 2404–2417 (1984).
- [44] K. Merboldt, Wolfgang Hanicke, and Jens Frahm (1969), “Self-diffusion NMR imaging using stimulated echoes,” *Journal of Magnetic Resonance*, **64** (3), pp. 479-486.
- [45] Nicholas Metropolis, Arianna W. Rosenbluth, Marshall N. Rosenbluth, Augusta H. Teller, and Edward Teller (1953), “Equation of State Calculations by Fast Computing Machines,” *Journal of Chemical Physics*. The previous link is to the Americain Institute of Physics and if you do not have access to Science Sitations you many not be able to retrieve this paper.
- [46] Radford M. Neal (1993), “Probabilistic Inference Using Markov Chain Monte Carlo Methods,” technical report CRG-TR-93-1, Dept. of Computer Science, University of Toronto.
- [47] Jeffrey J. Neil, and G. Larry Bretthorst (1993), “On the Use of Bayesian Probability Theory for Analysis of Exponential Decay Data: An Example Taken from Intravoxel Incoherent Motion Experiments,” *Magn. Reson. in Med.*, **29**, pp. 642–647.
- [48] H. Nyquist (1924), “Certain Factors Affecting Telegraph Speed,” *Bell System Technical Journal*, **3**, pp. 324-346.
- [49] H. Nyquist (1928), “Certain Topics in Telegraph Transmission Theory,” *Transactions AIEE*, **3**, pp. 617-644.
- [50] William H. Press, Saul A. Teukolsky, William T. Vetterling and Brian P. Flannery (1992), “Numerical Recipes The Art of Scientific Computing Second Edition,” Cambridge University Press, Cambridge UK.
- [51] Emanuel Parzen (1962), “On Estimation of a Probability Density Function and Mode,” *Annals of Mathematical Statistics* **33**, 1065–1076
- [52] Karl Pearson (1895), “Contributions to the Mathematical Theory of Evolution. II. Skew Variation in Homogeneous Material,” *Phil. Trans. R. Soc. A* **186**, 343–326.

- [53] Murray Rosenblatt, "Remarks on Some Nonparametric Estimates of a Density Function," *Annals of Mathematical Statistics* **27**, 832–837 (1956).
- [54] Jeffery D. Scargle (1981), "Studies in Astronomical Time Series Analysis I. Random Process In The Time Domain," *Astrophysical Journal Supplement Series*, **45**, pp. 1-71.
- [55] Jeffery D. Scargle (1982), "Studies in Astronomical Time Series Analysis II. Statistical Aspects of Spectral Analysis of Unevenly Sampled Data," *Astrophysical Journal*, **263**, pp. 835-853.
- [56] Jeffery D. Scargle (1989), "Studies in Astronomical Time Series Analysis. III. Fourier Transforms, Autocorrelation Functions, and Cross-correlation Functions of Unevenly Spaced Data," *Astrophysical Journal*, **343**, pp. 874-887.
- [57] Arthur Schuster (1905), "The Periodogram and its Optical Analogy," *Proceedings of the Royal Society of London*, **77**, p. 136-140.
- [58] Claude E. Shannon (1948), "A Mathematical Theory of Communication," *Bell Syst. Tech. J.*, **27**, pp. 379-423.
- [59] John E. Shore, and Rodney W. Johnson (1981), "Properties of cross-entropy minimization," *IEEE Trans. on Information Theory*, **IT-27**, No. 4, pp. 472-482.
- [60] John E. Shore and Rodney W. Johnson (1980), "Axiomatic derivation of the principle of maximum entropy and the principle of minimum cross-entropy," *IEEE Trans. on Information Theory*, **IT-26** (1), pp. 26-37.
- [61] Devinderjit Sivia, and John Skilling (2006), "Data Analysis: A Bayesian Tutorial," Oxford University Press, USA.
- [62] Edward O. Stejskal and Tanner, J. E. (1965), "Spin Diffusion Measurements: Spin Echoes in the Presence of a Time-Dependent Field Gradient." *Journal of Chemical Physics*, **42** (1), pp. 288-292.
- [63] D. G. Taylor and Bushell, M. C. (1985), "The spatial mapping of translational diffusion coefficients by the NMR imaging technique," *Physics in Medicine and Biology*, **30** (4), pp. 345-349.
- [64] Myron Tribus (1969), "Rational Descriptions, Decisions and Designs," Pergamon Press, Oxford.
- [65] P. M. Woodward (1953), "Probability and Information Theory, with Applications to Radar," McGraw-Hill, N. Y. Second edition (1987); R. E. Krieger Pub. Co., Malabar, Florida.
- [66] Arnold Zellner (1971), "An Introduction to Bayesian Inference in Econometrics," John Wiley and Sons, New York.

Index

- A_k definition, 349
- $H_{j\ell}(t_i)$ definition, 349
- λ_ℓ definition, 349
- g_{jk} eigenvalue, 349
- Abscissa, **437**
 - Computational, 436
 - Generating, 427
 - Loading, 39
 - Multicolumn, 437
 - Number Of Columns, 458
 - Total Data Values, 456
- Aliases, 113, **126**
- Amplitudes orthonormal definition, 349
- Analyze Image Pixel Package, **411**
 - Modification History, 413
 - Phased Images, 397
 - Reports
 - Bayes Accepted, 413
 - Using, 413
 - Viewers
 - Fortran/C Models, 411
 - Image, 411
 - Prior Probabilities, 413
 - Widgets
 - Abscissa File, 411
 - Build, 411
 - Find Outliers, 411
 - Get Statistics, 413
 - System, 411
 - User, 411
- Analyze Image Pixel Unique Package, **423**
 - Highlight
 - Abscissa, 425
 - Data, 425
 - Input Image
 - Abscissa, 423
 - Data, 423
 - Reports
 - Bayes Accepted, 425
 - Console Log, 425
 - McMC Values, 425
 - Using, 425
 - Viewers
 - Fortran/C Models, 423
 - Image, 423
 - Prior Probabilities, 425
 - Widgets
 - Build, 423
 - Find Outliers, 423
 - Get Statistics, 425
 - System, 423
 - User, 423
- Ascii Data Viewer, **53**
- Assigning Probabilities, **118**
- Bandwidth, **111, 127**
- Bayes Analyze Package, **155**
 - Levenberg-Marquardt , 171
 - Step, 194
 - Algorithm, 175
 - Amplitudes, 197, 198
 - Bayes Model, 159, 161
 - Bayesian Calculations, 167
 - Bruker, 162
 - Build BA Model, 159
 - Covariance, 174
 - Default Parameters Settings, 155
 - Error Messages, 200
 - Fid Model Viewer, 160
 - Interface, 156
 - Likelihood
 - Gaussian, 158
 - Student's t -distribution, 158

- Log File, [193](#), [195](#)
- Lorentzian lineshape, [161](#)
- Marking Resonances, [157](#)
- Model
 - J_o , [165](#)
 - J_p , [165](#)
 - J_s , [165](#)
 - Amplitude, [163](#), [164](#)
 - Bessel Function, [163](#)
 - Constants Models, [157](#)
 - Correlated, [157](#), [162](#), [164](#)
 - Equation, [161](#), [164](#), [164](#)
 - First Order Phase, [157](#), [162](#), [164](#)
 - First Point, [162](#), [164](#)
 - Gaussian, [163](#)
 - Imaginary Constant, [164](#)
 - Multi-Exponential, [163](#)
 - Multiple Data Sets, [165](#)
 - Multiplet Order, [164](#)
 - Multiplet Orders, [164](#)
 - Multiplets, [162](#)
 - Multiplets of Multiplets, [164](#)
 - Non-Lorentzian, [163](#)
 - Offsets, [162](#)
 - Real Constant, [164](#)
 - Relative Amplitude, [164](#)–[166](#)
 - Resonance Frequency, [165](#)
 - Shim Order, [163](#)
 - Shimming, [166](#)
 - Shimming Order, [164](#)
 - Uncorrelated, [157](#), [162](#), [164](#)
 - Zero Order Phase, [157](#), [162](#), [164](#)
- Model Interface, [160](#)
- Multiplets, [158](#)
- Newton-Raphson, [171](#)
- Noise File, [158](#)
- Noise Standard Deviation, [158](#)
- Outputs
 - Bayes.accepted File, [177](#)
 - bayes.log.nnnn File, [177](#), [193](#), [193](#)
 - bayes.model.nnnn File, [177](#), [185](#), [197](#), [197](#)
 - bayes.noise File, [180](#)
 - bayes.noise.nnnn File, [158](#), [180](#)
 - bayes.output.nnnn File, [176](#), [186](#), [186](#)
 - bayes.params File, [176](#), [177](#)
 - bayes.params.nnnn File, [176](#), [177](#), [177](#)
 - bayes.probabilities.nnnn File, [177](#), [190](#), [190](#)
 - bayes.status.nnnn File, [177](#), [196](#), [200](#)
 - bayes.summary1.nnnn File, [177](#), [198](#), [198](#)
 - bayes.summary2.nnnn File, [177](#), [199](#), [199](#)
 - bayes.summary3.nnnn File, [177](#), [200](#), [200](#)
 - Global Parameters, [182](#), [183](#)
 - Model File, [184](#)
 - Probabilities file, [191](#)
 - Zero Order Phase, [182](#)
- Parameter File
 - Activate Shims, [180](#)
 - Analysis Directory, [178](#)
 - By Fid, [181](#)
 - Data Type, [180](#)
 - Default Model, [181](#)
 - Directory Organization, [180](#)
 - Fid Model Name, [178](#)
 - File Version, [178](#)
 - First Fid, [181](#)
 - First Order Phase, [180](#), [183](#)
 - Imaginary Constant, [184](#)
 - Last Fid, [181](#)
 - lb, [182](#)
 - Maximum Candidates, [182](#)
 - Maximum New Resonances, [182](#)
 - Model Fid Number, [181](#)
 - Model Name, [184](#)
 - Model Names, [181](#)
 - Model Number, [184](#)
 - Model Points, [181](#)
 - Multiplets of Multiplets, [185](#)
 - Noise Start, [181](#)
 - Numerical Parameters, [178](#)
 - Output Format, [180](#)
 - Prior Odds, [182](#)
 - Procpair, [178](#)
 - Real Constant, [184](#)
 - Relative Amplitude, [183](#)
 - Resonance Model, [185](#)
 - Shim Order, [182](#)
 - Spectrometer Frequency, [182](#)
 - Text Parameters, [178](#)
 - Total Complex Data Values, [181](#)
 - Total Data Values, [181](#)
 - Total Sampling Time, [182](#)
 - True Reference, [182](#)

- Units, 180
- Use Noise StdDev, 180
- User Reference, 182
- Prior Probabilities, 167
- Probabilities File, 191
- Product Rule, 168
- Relative Amplitude, 167
- Remove Resonances, 159
- Reports
 - Bayes Status, 155
- Save/Reset, 159
- Search, 166
 - Levenberg-Marquardt , 166
- Short Parameter Description, 195
- Siemens, 162
- Status File, 196
- Steepest Descents, 173
- Sum Rule, 168
- Summary File, 198
- Summary Reports, 176
- Summary2, 199
- Summary3, 201
- Units, 161
- Using, 157
- Varian/Agilent, 162
- Widgets, 155
 - By, 158, 176
 - First Point, 157, 163
 - From, 158, 176
 - Imag Offset, 163
 - Imaginary Offset, 157
 - Mark, 159
 - Max New Res, 157
 - New, 159
 - Noise, 158
 - Phase, 157
 - Primary, 158
 - Real Offset, 157, 163
 - Remove, 159
 - Remove All, 159
 - Reset, 159, 193
 - Restore, 159
 - Save, 159
 - Secondary, 159
 - Shim Order, 157, 163
 - Signal, 158
 - To, 158, 176
- Bayes Find Resonances Package, **239**
 - Bayesian Calculations, 241
 - Current Fid, 239
 - Model Equation, 241
 - Number of data sets, 239
 - Phase Model
 - Automatic, 239, 242
 - Common, 239, 242
 - Independent, 239, 242
 - Prior Probabilities, 243–245
 - Reports
 - Bayes Accepted, 241, 246
 - Condensed, 246
 - Console log, 246
 - MCMC Values, 246
 - Prob Model, 246
 - Using, 239, 241
 - Viewers
 - Fid Data, 240
 - Fid Model, 240, 246
 - File, 246
 - Plot Results, 246
 - Text, 246
 - Widgets
 - Build FID Model, **240, 241, 246**
 - Constant, 239, 242
 - First Trace, 239
 - Last Trace, 239
 - Model Fid Number, 241
 - Phase Model, 239, 242
- Bayes Home Directory, 45, **49**
- Bayes Manual pdf, 469
- Bayes Metabolite Package
 - Widgets
 - Shift Left, 222
 - Shift Right, 222
- Bayes Metabolite Package, **219**
 - Aligning Resonances, 221
 - Bayesian Calculation, 225
 - Metabolite Locations, 221
 - Model Equation, 223
 - Reports
 - Bayes Accepted, 221, 238
 - Condensed, 238
 - Console log, 238

- McMC Values, [238](#)
- Prob Model, [238](#)
- Viewers
 - Fid Data, [219](#)
 - Fid Model, [221](#), [236](#)
 - File, [222](#), [238](#)
 - Metabolite, [221](#)
 - Plot Results, [238](#)
 - Text, [238](#)
- Widgets
 - Fid Model, [221](#)
 - Fid Model Viewer, [221](#)
 - Load System Metabolite File, [219](#)
 - Load System Resonance File, [221](#)
 - Load User Metabolite File, [219](#)
 - Load User Resonance File, [221](#)
 - Shift Left, [221](#)
 - Shift Right, [221](#)
- Bayes Model, [159](#), [159](#)
- Bayes Test Data Package, [427](#)
 - Parameters, [431](#)
 - Reports
 - Bayes Accepted, [428](#)
 - Condensed, [429](#)
 - McMC Values, [429](#), [431–433](#)
 - Viewers
 - Fortran/C Models, [427](#)
 - Image, [428](#)
 - Prior Probabilities, [427](#)
 - Text Data, [430](#)
 - Text Results, [429](#)
 - Widgets
 - # Images, [427](#)
 - # Slices, [427](#)
 - Abscissa, [427](#)
 - ArrayDim, [427](#)
 - Build, [427](#)
 - Get Job, [428](#)
 - Max Value, [427](#)
 - Noise SD, [427](#)
 - Parameter Ranges, [428](#)
 - Pe, [427](#)
 - Ro, [427](#)
 - Run, [428](#)
 - Set (server), [428](#)
 - Status, [428](#)
- Bayes' Theorem, [100](#), [139](#), [145](#), [153](#), [167](#), [211](#), [226](#), [243](#), [252](#), [261](#), [269](#), [278](#), [288](#), [295](#), [306](#), [314](#), [315](#), [317](#), [318](#), [331](#), [333](#), [343](#), [370](#), [399](#), [407](#), [439](#)
- Bayes.accepted
 - Body, [77](#)
 - Header, [76](#)
- Behrens-Fisher Package, [311](#)
 - Bayesian Calculations
 - Derived Probabilities, [320](#)
 - Different Mean And Same Variance, [318](#)
 - Different Mean And Variance, [319](#)
 - Parameter Estimation, [321](#)
 - Same Mean And Different Variance, [317](#)
 - Same Mean And Variance, [315](#)
 - Model Equation
 - Different Mean And Same Variance, [318](#)
 - Different Mean And Variance, [319](#)
 - Same Mean And Different Variance, [317](#)
 - Same Mean And Variance, [315](#)
 - Number of data sets, [311](#)
 - Parameter Listing, [323](#)
 - Prior Probabilities
 - Different Mean And Same Variance, [318](#)
 - Different Mean And Variance, [319](#)
 - Same Mean And Different Variance, [317](#)
 - Same Means And Same Variance, [315](#)
 - Reports
 - Bayes Accepted, [311](#), [322](#)
 - Condensed, [322](#)
 - Console Log, [322](#), [323](#)
 - McMC Values, [322](#), [323](#)
 - Prob Model, [322](#)
 - Using, [311](#)
- Viewers
 - File, [322](#)
 - Plot Results, [322](#), [324](#)
 - Prior Probabilities, [311](#)
 - Text, [322](#)
- Widgets
 - None, [311](#)
- Big Endian, [471](#), [473](#)
- Big Magnetization Transfer Package, [259](#)
 - Bayesian Calculations, [259](#)
 - Files
 - Bayes Analyze, [264](#)

- Fid, [263](#)
- Peak Pick, [262](#)
- Model Equation, [261](#)
- Number of data sets, [259](#)
- Prior Probabilities, [261](#)
- Reports
 - Bayes Accepted, [259](#), [262](#)
 - Condensed, [262](#)
 - Console log, [262](#)
 - McMC Values, [262](#)
 - Prob Model, [262](#)
- Using, [259](#)
- Viewers
 - Ascii Data, [259](#)
 - File, [262](#)
 - Prior Probabilities, [259](#)
 - Text, [262](#)
- Widgets
 - Find Outliers, [259](#)
- Big Peak/Little Peak Package, [207](#)
- Bayesian Calculations, [209](#)
- Fid Analyzed, [207](#)
- Model Equation, [210](#)
 - Metabolites, [209](#)
 - Solvent, [210](#)
- Number of data sets, [207](#)
- Prior Probabilities
 - Metabolite, [207](#)
 - Solvent, [207](#)
- Removing Resonances, [207](#)
- Reports
 - Bayes Accepted, [209](#), [216](#)
 - Condensed, [216](#)
 - Console log, [216](#)
 - McMC Values, [216](#)
 - Prob Model, [216](#)
- Using, [207](#)
- Viewers
 - File, [216](#)
 - Model, [209](#)
 - Plot Results, [216](#)
 - Prior Probabilities, [207](#)
 - Text, [216](#)
- Widgets
 - Metabolite, [207](#)
 - Solvent, [207](#)
- Binned Density Function Estimation, [355](#)
- Binned Histogram Package
 - Reports
 - Bayes Accepted, [357](#)
 - Viewers
 - Ascii, [355](#)
- Binned Histograms Package
 - Using, [357](#)
 - Viewers
 - Prior Probabilities, [355](#)
- Bloch-McConnell Equations, [267](#), [277](#)
- Changing the Bayes Home Directory, [469](#)
- Compilers, [29](#)
 - CC, [29](#), [455](#)
 - Fortran, [29](#), [455](#)
- Correlations, [91](#)
- Diffusion Tensor Package, [247](#)
 - Ascii File Formats, [247](#), [254](#), [255](#)
 - Bayesian Calculations, [249](#)
 - Prior Probabilities
 - Δ , [254](#)
 - Γ , [254](#)
 - δ , [254](#)
 - σ , [253](#)
 - Amplitudes, [253](#)
 - Eigenvalues, [253](#)
 - Euler Angles, [253](#)
 - Likelihood, [253](#)
 - Parameter, [254](#)
 - Reports
 - Bayes Accepted, [247](#), [255](#)
 - Condensed, [255](#)
 - Console log, [255](#)
 - McMC Values, [255](#)
 - Prob Model, [255](#)
 - Symmetries, [253](#)
 - Using, [247](#)
 - Viewers
 - File, [247](#), [255](#)
 - Plot Results, [255](#)
 - Prior Probabilities, [247](#), [253](#)
 - Text, [255](#)
 - Widgets
 - Abscissa Options, [248](#)

- Find Outliers, 247
- Include Constant, 247, 248, 255
- Tensor Number, 247, 248, 255
- Use b Matrix, 255
- Use b Vectors, 255
- Use g Vectors, 254
- Discrete Fourier Transform, 110, 113, 123
- Enter Ascii Model Package, **329**
 - Bayesian Calculations, 332
 - Marginalization, 332
 - No Marginalization, 331
 - Fortran/C Models, 330, 335
 - Model Equation
 - Marginalization, 331
 - No Marginalization, 331
 - Output Names
 - Derived, 335
 - Parameters, 335
 - Reports
 - Bayes Accepted, 331, 335
 - Bayes Params, 335
 - Condensed, 335
 - Console log, 335
 - McMC Values, 335
 - Prob Model, 335
 - Using, 331
 - Viewers
 - Ascii Data, 329
 - File, 335
 - Fortran/C Models, 329
 - Plot Results, 335
 - Prior Probabilities, 329
 - Text, 335
 - Widgets
 - Build, 329
 - Find Outliers, 329
 - System, 329
 - User, 329
- Enter Ascii Model Selection Package, **341**
 - Bayesian Calculations
 - Marginalization, 346
 - No Marginalization, 344
 - Fortran/C Models, 341, 343, 353
 - Model Equation, 343
 - No Marginalization, 343
 - With Marginalization, 347
 - Output Names
 - Derived, 354
 - Parameters, 353
 - Reports
 - Bayes Accepted, 343, 353
 - Condensed, 353
 - Console log, 353
 - McMC Values, 353
 - Params File, 353
 - Prob Model, 353
 - Using, 343
 - Viewers
 - Ascii Data, 341
 - File, 353
 - Fortran/C Models, 341
 - Plot Results, 353
 - Prior Probabilities Not Used, 341
 - Text, 353
 - Widgets
 - Build Not Used, 341
 - Find Outliers, 341
 - System, 341
 - User, 341
- Errors In Variables Package, **303**
 - Ascii File Formats
 - Errors In X and Y Known, 303, 309
 - Errors In X Known, 303, 309
 - Errors In Y Known, 303, 309
 - Errors Unknown, 303, 309
 - Bayesian Calculations, 305
 - Data Error Bars, 303
 - Files
 - Ascii, 303
 - Bayes Analyze, 303
 - Peak Pick, 303
 - Model Equation, 305
 - Number of data sets, 303
 - Reports
 - Bayes Accepted, 305, 309
 - Condensed, 309
 - Console log, 309
 - McMC Values, 309
 - Prob Model, 309
 - Using, 305
 - Viewers

- Ascii Data, [303](#)
 - File, [309](#)
 - Plot Results, [309](#)
 - Text, [309](#)
- Widgets
 - Given Errors In, [303](#)
 - Order, [303](#)
- Exponentials
 - Given Package, [137](#)
 - Inversion Recovery Package, [151](#)
 - Magnetization Transfer Package, [267](#)
 - Unknown Number of Package, [143](#)
- Fid Data Viewer, [53](#)
- Fid Model Viewer, [68](#)
- File Format
 - Ascii, [436](#)
- File Viewer, [80](#)
- Files
 - 4dfp, [59](#), [428](#), [430](#), [470](#), [471](#)
 - Header, [473](#)
 - Reading, [471](#)
 - Abscissa, [39](#), [77](#), [470](#)
 - afh, [53](#)
 - ASCII, [35](#), [36](#)
 - Ascii, [53](#), [54](#), [435](#)
 - k*-space, [437](#)
 - Abscissa, [435](#), [436](#), [437](#)
 - Data, [435](#)
 - Image, [436](#)
 - Bayes Analyze, [36](#)
 - Bayes.accepted, [51](#), [76](#)
 - Bayes.params, [76](#), [79](#)
 - Bayes.prob.model, [447](#)
 - BayesManual.pdf, [469](#)
 - Condensed, [77](#), [78](#)
 - Console.log, [76](#), [79](#), [465](#)
 - dir.info, [470](#)
 - fid, [470](#), [470](#)
 - ASCII, [36](#)
 - ffh, [56](#)
 - Model, [68](#), [70](#)
 - procpa, [470](#)
 - Siemens Raw, [36](#)
 - Siemens Rda, [36](#)
 - Spectroscopic, [53](#)
 - Varian fid, [36](#)
 - Fortran/C Models, [42](#), [455](#), [457](#), [458](#), [465](#)–[467](#)
 - Images
 - 4dfp, [38](#)
 - Binary, [38](#)
 - Bruker 2dseq, [38](#)
 - Bruker stack, [38](#)
 - DICOM, [38](#)
 - FDF, [38](#)
 - Multi-Column Text, [38](#)
 - Siemens IMA, [38](#)
 - k*-space
 - Text, [36](#)
 - Varian fid, [36](#)
 - mcmc.values, [76](#), [449](#)
 - Model Listing, [77](#)
 - prob.model, [76](#)
 - procpa, [470](#)
 - Raw, [36](#)
 - RDA, [36](#)
 - Statistics, [65](#)
 - System.err.txt, [469](#)
 - System.out.txt, [469](#)
 - Varian fid, [36](#)
 - WaterViscosityTable, [469](#)
- Fortran/C Model Viewer, [93](#)
 - Popup Editor, [93](#)
- Fortran/C Models, [42](#), [330](#), [335](#), [353](#), [455](#)
 - Abscissa, [463](#)
 - Body, [463](#)
 - Abscissa, [457](#)
 - Declarations, [462](#)
 - Derived Parameters, [457](#), [459](#), [463](#)
 - Edit/Create New Model, [42](#), [455](#)
 - I/O, [464](#)
 - Marginalization, [464](#)
 - $G_j(\Omega, t_i)$, [464](#)
 - Amplitude Range, [465](#)
 - Example, [465](#), [466](#)
 - Model Vectors, [465](#)
 - Ordering Amplitudes, [465](#)
 - Parameter File, [465](#), [467](#)
 - Parameter Order, [465](#)
 - Parameters, [465](#)
- Model Files, [455](#)

- Model Selection, 464
- No Marginalization, 457
 - $S(t_i)$, 455
 - Example, 456
- Parameter File, 458, 459, 465
- Parameters, 463
- Signal, 463
- Subroutine Interface, 460
 - Abscissa, 462
 - Current Set, 460
 - Derived Parameters, 461
 - Maximum No Of Data Values, 461
 - Number Of Abscissa Columns, 461
 - Number Of Data Columns, 461
 - Number Of Derived Parameters, 461
 - Number Of Model Vectors, 461
 - Number Of Parameters, 460
 - Parameters, 461
 - Signal, 462
 - Total Complex Data Values, 461
- Subroutines and Functions, 464
- Frequency Estimation, 114, 132
- Given Exponential Package, 137
 - Bayesian Calculations, 140
 - Files
 - Ascii, 137
 - Bayes Analyze, 137
 - Peak Pick, 137
 - Model Equation, 139
 - Number of data sets, 139
 - Prior Probabilities, 139–141
 - Reports
 - Bayes Accepted, 137, 141
 - Condensed, 141
 - Console log, 141
 - McMC Values, 141
 - Prob Model, 141
 - Symmetries, 141, 148
 - Using, 137
 - Viewers
 - File, 141
 - Plot Results, 141
 - Prior Probabilities, 137, 139
 - Text, 141
 - Widgets
- Constant, 137, 139
- Find Outliers, 137
- Given Order, 27
- Include Constant, 27
- Order, 137, 139
- Given Polynomial Order Package, 285
 - Bayesian Calculations, 288
 - Files
 - Ascii, 285
 - Bayes Analyze, 285
 - Peak Pick, 285
 - Gram-Schmidt, 287
 - Model Equation, 287
 - Number of data sets, 285
 - Prior Probabilities, 289
 - Reports
 - Bayes Accepted, 285, 291
 - Condensed, 291
 - Console log, 291
 - McMC Values, 291
 - Prob Model, 291
 - Scatter Plots, 292
 - Using, 285
 - Viewers
 - File, 290
 - Plot Results, 291
 - Text, 290
 - Widgets
 - Set Order, 285
- Histograms
 - Binned, 381
 - Kernel Density, 381
- Image Model Selection Package, 415
 - Abscissa, 415
 - Fortran/C Models, 415, 417
 - Reports
 - Bayes Accepted, 417
 - Using, 417
 - Viewers
 - Fortran/C Models, 415
 - Image, 415
 - Widgets
 - Noise SD, 415
 - System, 415

- Use Gaussian, 415
- User, 415
- Image Viewer, 59
- Images
 - Flip
 - Horizontal, 63
 - Vertical, 63
 - Grayscale, 63
 - ImageJ, 63
 - Original, 63
- Inversion Recovery Package, 151
 - Bayesian Calculations, 153
 - Model Equation, 153
 - Number of data sets, 153
 - Prior Probabilities, 153
 - Reports
 - Bayes Accepted, 151, 154
 - Condensed, 154
 - Console Log, 154
 - McMC Values, 154
 - Prob Model, 154
 - Using, 151
 - Viewers
 - Plot Results, 154
 - Prior Probability, 151
 - Widgets
 - Find Outliers, 151
- Kernel Density Function Package, 361
 - Ascii File Format, 361
 - Bayesian Calculations, 369
 - Data Requirements, 361
 - Data, Model And Residuals, 369
 - Kernels, 369
 - Biweight, 362
 - Cosine, 362
 - Epanechnikov, 362
 - Exponential, 362
 - Gaussian, 362, 370
 - nonnegative, 361
 - Real Valued, 361
 - Triangular, 362
 - Tricube, 362
 - Triweight, 362
 - Uniform, 362
 - Likelihood, 371
 - Number of data sets, 364
 - Plots
 - Expected Density Function, 367, 368
 - Mean Density Function, 367, 368
 - Posterior Probability for the Kernel Type, 365
 - Posterior Probability for the Number Of Kernels, 366
 - Scatter Plots of Model Averaged Density Function, 368
 - Standard Deviation of the Mean Density Function, 367, 368
 - Prior Probabilities
 - Kernel Center, 371
 - Kernel Smoothing Parameter, 371
 - Kernel Type, 370
 - Number Of Kernels, 370
 - Reports
 - Bayes Accepted, 364
 - Condensed, 372
 - McMC Values, 372
 - Prob Model, 372
 - Using, 364
 - Viewers
 - Ascii, 361
 - Widgets
 - Kernel Type, 364
 - Output Size, 364
- Levenberg-Marquardt, 171
- Linear Phasing Package, 395, 409
 - Interface, 397
 - Model Equation, 398
 - Widgets
 - cf, 403
 - Display, 403
 - Display Array Element, 403
 - fn, 403
 - fn1, 403
 - Image Type, 402
 - Load An Image, 402
 - np, 403
 - nv, 403
 - Process, 403
 - Load Working Directory, 33
 - Logical Independence, 117

- Magnetization Transfer Kinetics Package, **275**
 - Arrhenius Plot, **281**
 - Bayesian Calculation, **278**
 - Boltzmann's Constant, **277**
 - Eyring Equation, **275, 276, 277, 280**
 - Model Equation, **277**
 - Plank's Constant, **277**
 - Prior Probabilities, **279**
 - Reports
 - Bayes Accepted, **277, 281**
 - Condensed, **281**
 - Console log, **281**
 - McMC Values, **281**
 - Prob Model, **281**
 - Sum and Difference Variables, **280**
 - Transmission coefficient, **277**
 - Universal Gas Constant, **277**
 - Using, **277**
 - van't Hoff Plot, **281**
 - Viewers
 - Ascii File, **275**
 - File, **281**
 - Prior Probabilities, **275**
 - Text, **281**
 - Widgets
 - Load, **275, 281**
 - Set, **275**
 - Uncertainty, **275**
- Magnetization Transfer Package, **265**
 - Bayesian Calculations, **267**
 - Files
 - Ascii, **265**
 - Bayes Analyze, **265**
 - Inversion Recovery, **272**
 - Peak Pick, **265**
 - Model Equation, **267**
 - Number of data sets, **265**
 - Prior Probabilities, **265, 270**
 - Reports
 - Bayes Accepted, **267, 272**
 - Condensed, **272**
 - Console log, **272**
 - McMC Values, **272**
 - Prob Model, **272**
 - Three Column Data, **265**
 - Using, **267**
- Viewers
 - Ascii Data, **265**
 - Fid Data, **272**
 - File, **271**
 - Plot Results, **262, 272, 281**
 - Prior Probabilities, **265**
 - Text, **271**
- Widgets
 - Find Outliers, **265**
- Marginalization, **100**
 - Bayes Analyze Package, **174**
 - Behrens-Fisher, **315**
 - Big Magnetization Transfer, **261**
 - Big Peak/Little Peak, **211**
 - Diffusion Tensors, **252**
 - Enter Ascii Model Package, **331**
 - Errors In Variables, **306**
 - Fortran/C Models, **464**
 - Given Exponential, **139**
 - Inversion Recovery, **153**
 - Linear Phasing, **399**
 - Magnetization Transfer, **269**
 - Magnetization Transfer Kinetics, **278**
 - Metabolic Analysis, **225**
 - Nonexhaustive Hypotheses, **101**
 - Nuisance Hypotheses, **100**
 - Nuisance Parameter, **100**
 - Unknown Number of Exponentials, **146**
- Markov chain Monte Carlo, **132, 439**
 - Acceptance Rate, **444**
 - Annealing Schedule, **91, 442**
 - Dynamic, **443**
 - Linear, **442**
 - Killing Simulations, **443**
 - Maximum Posterior Probability, **91**
 - Metropolis-Hastings, **439**
 - Mixing, **91**
 - Monte Carlo Integration, **440**
 - Multiple Simulations, **441**
 - Posterior Probability, **440**
 - Random Number Generators, **440**
 - Repeats, **91**
 - Sampling, **91**
 - Simulated Annealing, **442**
 - the Proposal, **444**

- MaxEnt Density Function Estimation Package, **373**
 - Data Requirements, **381**
 - Plots
 - Contour/Scatter, **375, 379**
 - Number Of Multipliers, **375, 378**
 - Reports
 - Bayes Accepted, **375**
 - Console Log, **375**
 - Using, **375**
 - Viewers
 - Ascii, **373**
 - Plot, **375, 378**
 - Prior Probabilities, **373**
 - Widgets
 - Histogram Size, **373**
 - Order, **373**
- Maximum Entropy Method Of Moments, **102, 377, 381**
 - Advantages, **386**
 - Problems, **386**
 - Review, **381**
- Maximum Entropy Method Of Moments Package
 - Bayesian Calculations, **387**
 - Plots
 - Data, Model and Residuals, **380**
- Menus
 - Files, **24, 35**
 - 4dfp, **37, 38**
 - Abscissa, **35, 39**
 - ASCII, **35, 36**
 - Binary, **38**
 - Bruker, **37**
 - Bruker 2dseq, **38**
 - Bruker Stack, **38**
 - DICOM, **37, 38**
 - FDF, **37, 38**
 - fid, **36, 37**
 - General Binary, **37**
 - Images, **35**
 - Import Working Directories in Batch, **40**
 - Import Working Directory, **40**
 - Load Images, **36, 37, 59**
 - Load Working Directory, **35**
 - Multi-Column Text, **37, 38**
 - Save Working Directory, **35, 39**
 - Siemens IMA, **37, 38**
 - Single-Column Text, **38**
 - Spectroscopic Fid, **35**
 - Test Data, **35, 39**
 - Text k-space, **36**
 - Text k-space fid, **37**
 - User Manual, **35, 39**
- Help, **24**
- Packages, **22, 24, 33, 40**
- Settings, **46**
 - Add Server, **48**
 - Auto Configure Server, **48**
 - MCMC Parameters, **24, 46, 48**
 - Min Annealing Steps, **48, 48**
 - Port number, **48**
 - Preferences, **49, 63**
 - Remove Server, **48, 49**
 - Repetitions, **46, 48**
 - Server Name, **48**
 - Server Setup, **24, 26, 48**
 - Set Window Size, **49**
 - Simulations, **46, 48**
 - View Server Installation Info, **48, 49**
- Spectroscopy fid, **36**
- Utilities, **24, 50**
 - Memory Monitor, **50**
 - Software Updates, **50**
 - System Information, **50**
- WorkDir
 - Creating, **22, 33, 46**
 - Deleting, **22, 33, 46**
 - List, **24, 46**
 - Loading, **46**
 - Name, **46**
 - Popup, **47**
- Model Comparison
 - Big Peak/Little Peak Package, **211**
- model orthonormal definition, **349**
- Mouse
 - Control-left, **59**
- Fid Data Viewer
 - Left, **56**
 - Right, **56**
 - Shift-left, **59**
- Multiplets
 - J-Coupling

- Center, [159](#)
- Primary, [159](#)
- Secondary, [159](#)
- Newton-Raphson, [171](#)
- Noise Standard Deviation, [64](#)
- Non-Linear Phasing Package, [405](#)
 - Calculations, [407](#)
 - Model Equation, [405](#), [407](#)
 - Widgets
 - Process, [409](#)
 - Write Ascii images, [409](#)
 - Write imaginary images, [409](#)
- Nuisance Parameter, [100](#), [115](#), [135](#)
- Nyquist Critical Frequency, [111](#), [127](#)
- orthonormal, [349](#)
- Outliers, [475](#)
 - Mean Parameter, [477](#)
 - Model, [475](#)
 - Prob Number of, [476](#)
 - Proposal, [475](#)
 - Red dot, [477](#)
 - Weighted Average, [477](#)
- Packages
 - Analyze Image Pixel Unique, [423](#)
 - Bayes Analyze, [20](#), [43](#), [57](#), [155](#), [200](#)
 - Bayes Find Resonances, [21](#), [239](#)
 - Bayes Test Data, [427](#)
 - Behrens-Fisher, [21](#), [44](#), [311](#)
 - Big Magnetization Transfer, [20](#), [43](#), [259](#)
 - Big Peak/Little Peak, [20](#), [43](#), [207](#)
 - Binned Density Function Estimation, [355](#)
 - Binned Histograms, [21](#), [44](#)
 - Diffusion Tensors, [20](#), [40](#), [247](#)
 - Enter ASCII Model, [42](#)
 - Enter Ascii Model, [20](#), [329](#)
 - Enter ASCII Model Selection, [42](#)
 - Enter Ascii Model Selection, [20](#), [341](#)
 - Errors In Variables, [21](#), [44](#), [303](#)
 - Find Resonances, [43](#)
 - Given Exponential, [20](#), [40](#), [137](#)
 - Given Polynomial Order, [285](#)
 - Image Model Selection, [415](#)
 - Image Pixel, [21](#), [45](#), [411](#)
 - Image Pixel Model Selection, [22](#), [45](#)
 - Inversion Recovery, [20](#), [40](#), [151](#)
 - Kernel Density Function, [361](#)
 - Linear Phasing, [21](#), [44](#), [395](#)
 - Magnetization Transfer, [20](#), [42](#), [265](#)
 - Magnetization Transfer Kinetics, [20](#), [43](#), [275](#)
 - Maximum Entropy Method Of Moments, [21](#), [44](#), [373](#)
 - Metabolic Analysis, [21](#), [43](#), [219](#)
 - Non-Linear Image Phasing, [21](#), [45](#), [405](#)
 - Polynomials
 - of Given Order, [21](#), [44](#)
 - of Unknown Order, [21](#), [44](#)
 - Test ASCII Model, [42](#)
 - Test Ascii Model, [20](#), [337](#)
 - Unknown Number of Exponentials, [20](#), [40](#), [143](#)
 - Unknown Polynomial Order, [293](#)
- Parameter File, [42](#)
- Number Of
 - Abscissa, [458](#)
 - Data Columns, [458](#)
 - Model Vectors, [458](#)
 - Priors, [458](#)
- Prior Probability, [459](#)
 - Amplitude, [460](#)
 - High, [459](#)
 - Low, [459](#)
 - Mean, [459](#)
 - NonLinear, [460](#)
 - Ordered, [460](#)
 - Parameter File, [459](#)
 - Peak, [459](#)
 - Prior Type, [460](#)
 - Standard Deviation, [459](#)
- Phase Cycling, [162](#)
- Plot Results Viewer, [71](#)
- Plots
 - Data and Model, [81](#)
 - Data, Model and Residuals, [81](#)
 - Expected Log Likelihood, [88](#)
 - Logarithm of the Posterior Probability, [91](#)
 - Maximum Entropy Histogram, [84](#)
 - Maximum Entropy Histograms, [83](#)
 - McMC Samples, [83](#), [85](#)
 - Parameter Vs Posterior Probability, [86](#), [87](#)

- Posterior Probability, [82](#)
- Posterior Probability Vs Parameter Value, [86](#)
- Residuals, [81](#)
- Scatter, [88](#), [91](#)
- png graphics, [59](#)
- Posterior Probability Vs Parameter Value, [86](#)
- Power Spectrum, [112](#), [123](#), [124](#)
- Prior Probabilities
 - Bayes Phase, [399](#)
 - Big Magnetization Transfer, [261](#)
 - Big Peak/Little Peak, [212](#)
 - Diffusion Tensor, [253](#)
 - Enter Ascii Model, [331](#), [333](#)
 - Errors In Variables, [306](#)
 - Magnetization Transfer, [269](#)
 - Magnetization Transfer Kinetics, [279](#)
 - Non-Linear Phasing Package
 - A, [408](#)
 - θ , [408](#)
- Prior Probability, [42](#), [65](#), [65](#)
 - Exponential, [67](#), [459](#)
 - Gaussian, [67](#), [104](#), [106](#), [459](#)
 - Jeffreys', [118](#)
 - Normalization Constant, [67](#)
 - Parameter, [68](#), [459](#)
 - Positive, [68](#), [460](#)
 - Uniform, [67](#), [103](#), [118](#), [459](#)
- Prior Viewer, [65](#), [93](#)
- Probabilities
 - Expected Log Likelihood, [453](#)
 - Likelihood, [453](#)
 - Posterior, [453](#)
 - Prior, [453](#)
- Product Rule, [99](#), [119](#), [344](#), [439](#)
- Referencing
 - Setting, [59](#)
- Reports
 - Accepted File, [76](#)
 - McMC Values File
 - General Description, [449](#)
 - Maximum Posterior Probability Simulations, [451](#)
 - Mean Values, [452](#)
 - Prior, [450](#)
 - Standard Deviations, [453](#)
- Restoring An Analysis, [22](#), [35](#), [40](#)
- ROI
 - Expanding, [63](#)
 - Pixels, [63](#)
 - Point, [62](#)
 - Polygon, [62](#)
 - Square, [62](#)
- Saving An Analysis, [35](#), [39](#)
- Schuster Periodogram, [112](#), [123](#)
- Screen Captures, [49](#)
- Settings
 - httpd server, [19](#)
- Software
 - Bayes Account, [29](#)
 - CC, [29](#)
 - Fortran, [29](#)
 - Installation, [29](#)
 - javaws, [29](#)
 - OS requirements, [29](#)
 - root requirements, [30](#)
- Start Up Window, [22](#), [33](#)
- Steepest Descents, [173](#)
- Subdirectories, [469](#)
 - Bayes, [39](#)
 - Bayes.model.fid, [470](#)
 - Bayes.Predefined.Spec, [469](#)
 - Bayes.test.data, [39](#)
 - BayesAnalyzeFiles, [470](#)
 - BayesAsciiModels, [93](#), [469](#)
 - BayesOtherAnalysis, [35](#), [73](#), [470](#)
 - fid, [36](#), [53](#)
 - images, [36](#), [38](#), [39](#), [59](#), [470](#)
 - model.compile, [470](#)
 - plugins, [470](#)
 - Properties, [470](#)
 - Resources, [470](#)
 - Spectroscopic
 - fid, [470](#)
 - Working Directories, [470](#)
- Subroutine Names, [464](#)
- Sufficient Statistics, [122](#)
 - Definition, [105](#)
 - Location Parameter, [108](#)
- Sum Rule, [100](#), [119](#), [344](#), [440](#)

- Test Ascii Model Package, **337**
 - Reports
 - Bayes Accepted, **339**
 - Mcmc Values, **339**
 - Using, **339, 428**
 - Viewers
 - Ascii Data, **337**
 - Fortran/C Models, **337**
 - Prior Probabilities, **337**
 - Widgets
 - Build, **337**
 - Find Outliers, **339**
 - System, **337**
 - User, **337**
- Thermodynamic Integration, **445, 449**
- Uninstall, **49**
- Unknown Number of Exponentials Package, **143**
 - Bayesian Calculations, **145**
 - Model Equation, **145**
 - Reports
 - Bayes Accepted, **143, 148**
 - Condensed, **148**
 - Console Log, **148, 149**
 - McMC Values, **148**
 - Prob Model, **148**
 - Using, **143**
 - Viewers
 - File, **148**
 - Plot Results, **149, 150**
 - Prior, **143**
 - Text, **148**
 - Widgets
 - Constant, **143**
 - Find Outliers, **143**
 - Order, **143**
- Unknown Polynomial Order Package, **293**
 - Bayesian Calculations, **295**
 - Files
 - Ascii, **293**
 - Bayes Analyze, **293**
 - Peak Pick, **293**
 - Model Equation, **295**
 - Number of data sets, **293**
 - Reports
 - Bayes Accepted, **293, 299**
 - Condensed, **299**
 - Console Log, **298, 299**
 - McMC Values, **299**
 - Polynomial Order Plot , **301**
 - Prob Model, **299**
 - Using, **293**
 - Viewers
 - File, **299**
 - Text, **299**
 - Widgets
 - Set Order, **293, 294**
 - Unknown Order, **293, 294**
- Viewers, **27, 52**
 - ASCII Data, **36**
 - Ascii Data, **27, 53, 56, 63, 137, 265, 275, 285, 293, 311, 329, 337, 341**
 - Expanding Plot, **53**
 - Printing, **53**
 - Right click, **53**
 - Bayes Model, **160**
 - Fid Data, **27, 265**
 - fid Data, **53, 53, 285, 293**
 - Auto Range, **59**
 - Autoscale, **56**
 - Clear Cursors, **56**
 - Clear Data, **57**
 - Copy, **59**
 - Cursor, **56**
 - Data Info, **57**
 - Expand, **56**
 - fn, **57**
 - Full, **56**
 - Get Peak, **56**
 - Phase Popup, **57**
 - Print, **59**
 - Properties, **59**
 - Referencing, **59**
 - Save As, **57, 59**
 - Set Preference, **57**
 - Units, **59**
 - Zoom, **59**
 - Fid Model, **27**
 - fid Model, **68, 186**
 - Build BA Model, **70, 159**
 - Data, **71**

- Horizontal, 71
- Model, 71
- Overlay, 71
- Report, 71
- Residual, 71
- Stacked, 71
- Trace, 71
- Vertical, 71
- File, 28, 80
- Fortran/C Models, 93, 330
- Image, 27, 59, 415
 - Autoset Grayscale, 61
 - Copy Selected, 62
 - Delete All, 61
 - Delete Selected, 61
 - Display Full, 61
 - Element Selection, 60
 - Export, 62
 - Get Statistics, 64, 65
 - Get Threshold Statistics, 65
 - Grayscale, 63
 - Image Selection, 60
 - List, 59
 - Load Selected Pixels, 61
 - Max, 64
 - Mean, 64
 - Min, 64
 - Right Click, 61
 - RMS, 64
 - Save Displayed, 62
 - Save Statistics, 65
 - Sdev, 64
 - Set Image Area, 62
 - Show Histogram, 61
 - Show Info, 62
 - Slice, 62
 - Slice Selection, 60
 - Statistics, 60
 - Value, 64
 - View Selected Pixels, 61
 - Viewer Settings, 62
 - Viewing, 62
 - X Pos, 64
 - Y Pos, 64
- Plot Results, 28, 71
- Prior, 27, 65
 - Prior Probabilities, 138, 312
 - Text, 141, 271, 281, 290, 309, 322, 335, 353
 - Text Results, 26, 28, 52, 74
 - Bayes Analyze, 176
- Widgets
 - Analyze Image Pixel Package
 - Build, 411
 - Find Outliers, 411
 - Get Statistics, 413
 - System, 411
 - User, 411
 - Analyze Image Pixel Unique Package
 - Build, 423
 - Find Outliers, 423
 - Get Statistics, 425
 - System, 423
 - User, 423
 - Ascii Data Viewer
 - Delete, 53
 - Left-mouse, 53
 - Right-mouse, 53
 - Bayes Analyze Package
 - By, 158, 176
 - First Point, 163
 - From, 158, 176
 - Imag Offset, 163
 - Mark, 159
 - Max New Res, 157
 - New, 159
 - Noise, 158
 - Phase, 157
 - Primary, 158
 - Real Offset, 163
 - Remove, 159
 - Remove All, 159
 - Reset, 159, 193
 - Restore, 159
 - Save, 159
 - Secondary, 159
 - Shim Order, 157, 163
 - Signal, 158
 - To, 158, 176
 - Bayes Find Resonances Package
 - Build FID Model, 240, 241, 246
 - Constant, 239, 242

- First Trace, 239
- Last Trace, 239
- Model Fid Number, 241
- Phase Model, 239, 242
- Bayes Metabolite Package
 - Fid Model, 221
 - Fid Model Viewer, 221
 - Load System Metabolite File, 219
 - Load System Resonance File, 221
 - Load User Metabolite File, 219
 - Load User Resonance File, 221
 - Shift Left, 221, 222
 - Shift Right, 221, 222
- Bayes Test Data Package
 - # Images, 427
 - # Slices, 427
 - Abscissa, 427
 - ArrayDim, 427
 - Build, 427
 - Get Job, 428
 - Max Value, 427
 - Noise SD, 427
 - Pe, 427
 - Ro, 427
 - Run, 428
 - Set (server), 428
 - Status, 428
 - System, 427
 - User, 427
- Big Magnetization Transfer Package
 - Find Outliers, 259
- Big Peak/Little Peak Package
 - Metabolite, 207
 - Solvent, 207
- Diffusion Tensor Package
 - Abscissa Options, 248
 - Find Outliers, 247
 - Include Constant, 247, 248, 255
 - Tensor Number, 247, 248, 255
 - Use b Matrix, 255
 - Use b Vectors, 254, 255
 - Use g Vectors, 254
- Enter Ascii Model Package
 - Find Outliers, 329
 - System, 329
 - User, 329
- Enter Ascii Model Selection Package
 - Find Outliers, 341
 - System, 341
 - User, 341
- Errors In Variables Package
 - Given Errors In, 303
 - Order, 303
- Fid Data Viewer
 - Autoscale, 56
 - Clear Cursors, 56
 - Cursor A, 56
 - Cursor B, 56
 - Delta, 56
 - Display Type, 56
 - Expand, 56
 - Full, 56
 - Get Peak, 56
 - Left-mouse, 56
 - Options, 57, 59
 - Right-mouse, 56
 - Trace, 70
- Fortran/C Model Viewer
 - Abscissa Spinner, 93
 - Add Prior, 96
 - Allow/Disallow Editing, 97
 - Cancel and Exit, 96
 - Changing Models, 94
 - Code, 93, 94
 - Compile Results, 97
 - Compiling, 96
 - Create/Edit Model, 93
 - Data Columns Spinner, 93
 - Derived, 96
 - Edit/Create New Model, 93, 94
 - High, 97
 - Low, 97
 - Mean, 97
 - Model, 96
 - Model Vectors, 93
 - Name (parameter), 97
 - Order, 97
 - Parameter Type, 97
 - Parameters button, 93, 94, 96
 - Prior Type, 97
 - Priors, 96
 - Remove All (priors), 96

- Remove Prior, 96
- Remove Selected Model, 93
- Save and Load, 96
- Standard Deviation, 97
- Given Exponential Package
 - Constant, 137, 139
 - Find Outliers, 137
 - Order, 137, 139
- Given Polynomial Order Package
 - Set Order, 285
- Global
 - Bayes Find Outliers, 27
 - Cancel, 26, 51
 - Edit Servers, 26
 - Get Job, 26, 51, 137, 143, 151, 155, 209, 221, 241, 247, 259, 267, 277, 285, 293, 305, 311, 331, 339, 343, 357, 364, 373, 413, 417, 425, 428
 - Reset, 27
 - Restore Analysis, 22
 - Run, 26, 51, 137, 143, 151, 155, 207, 221, 241, 247, 248, 259, 267, 277, 285, 293, 305, 311, 329, 337, 343, 357, 364, 373, 413, 415, 425, 428
 - Save, 27
 - Set (server), 26, 52, 137, 143, 151, 155, 207, 221, 239, 247, 259, 265, 277, 285, 293, 305, 311, 329, 337, 343, 355, 364, 373, 413, 415, 425, 428
 - Status, 26, 52, 137, 143, 151, 155, 207, 221, 241, 247, 259, 267, 277, 285, 293, 305, 311, 329, 337, 343, 355, 364, 373, 413, 415, 425, 428
- Image Model Selection Package
 - System, 415
 - User, 415
- Image Viewer
 - Element Number, 62
 - Get Statistics, 64
 - Get Threshold Statistics, 65
 - Grayscale, 63
 - Save Statistics, 65
 - Slice Number, 62
 - Value, 64
 - X Pos, 64
 - Y Pos, 64
- Inversion Recovery Package
 - Find Outliers, 151
- Kernel Density Function Package
 - Kernel Type, 364
 - Output Size, 364
- Linear Phasing Package
 - cf, 403
 - Display, 403
 - Display Array Element, 403
 - fn, 403
 - fn1, 403
 - Image Type, 402
 - Load An Image, 402
 - np, 403
 - nv, 403
 - Process, 403
- Magnetization Transfer Kinetics Package
 - Load, 275, 281
 - Set, 275
 - Uncertainty, 275
- Magnetization Transfer Package
 - Find Outliers, 265
- MaxEnt Density Function Estimation Package
 - Histogram Size, 373
 - Order, 373
- Non-Linear Phasing Package
 - Process, 409
 - Write Ascii images, 409
 - Write imaginary images, 409
- Prior Viewer
 - High, 65
 - Low, 65
 - Mean, 65
 - Prior Type, 67
- Server
 - Edit, 52
 - Name, 26, 52, 52
 - Set (server), 48
 - Setup, 48, 52
- Test Ascii Model Package
 - Find Outliers, 339
 - System, 337
 - User, 337
- Text Results Viewer
 - Copy, 74

- Down arrow, [74](#)
- Enable Editing, [74](#)
- Print, [74](#)
- Save (a copy), [74](#)
- Save As, [74](#)
- Settings, [74](#)
- Up arrow, [74](#)
- Unknown Number of Exponentials Package
 - Constant, [143](#)
 - Find Outliers, [143](#)
 - Order, [143](#)
- Unknown Polynomial Order Package
 - Set Order, [293](#), [294](#)
 - Unknown Order, [293](#), [294](#)
- WorkDir
 - Creating, [22](#), [33](#), [46](#)
 - Deleting, [22](#), [33](#), [46](#)
 - List, [24](#), [46](#)
 - Loading, [46](#)
 - Name, [46](#)
 - Popup, [47](#)